



## Installation and Troubleshooting Guide

All rights reserved. Reproduction or use of content, in any manner, without express written permission by CDI Electronics, Inc., is prohibited.

### CDI P/N: 182-4475R

**Notice: This coil/bracket assembly replaces P/N's: 300-888791, F615475 and F684475.**

Warning! This product is designed for installation by a professional marine mechanic. CDI Electronics cannot be held liable for injury or damage resulting from improper installation, abuse, neglect or misuse of this product.

#### Installation

1. Remove the original coil, saving the original bolts, and cut off the primary lead (usually a white or blue striped wire) as close to the coil as possible.
2. Strip approximately ¼" of insulation from the primary lead.
3. Slide the heat shrink on the wire, then crimp and solder the #6 terminal to it.
4. Mount the new coil assembly from the bottom side of the plate using the original bolts.
5. Connect the new coil wire from the coil to the spark plug.
6. Connect the primary lead from the pack to the coil.

Thank you for choosing CDI Electronics

4/20/2009

CDI Electronics • 111 Commerce Circle • Madison, AL 35758  
Fax 256-772-5701 • www.cdielelectronics.com



## Installation and Troubleshooting Guide

All rights reserved. Reproduction or use of content, in any manner, without express written permission by CDI Electronics, Inc., is prohibited.

### CDI P/N: 182-4475R

**Notice: This coil/bracket assembly replaces P/N's: 300-888791, F615475 and F684475.**

Warning! This product is designed for installation by a professional marine mechanic. CDI Electronics cannot be held liable for injury or damage resulting from improper installation, abuse, neglect or misuse of this product.

#### Installation

1. Remove the original coil, saving the original bolts, and cut off the primary lead (usually a white or blue striped wire) as close to the coil as possible.
2. Strip approximately ¼" of insulation from the primary lead.
3. Slide the heat shrink on the wire, then crimp and solder the #6 terminal to it.
4. Mount the new coil assembly from the bottom side of the plate using the original bolts.
5. Connect the new coil wire from the coil to the spark plug.
6. Connect the primary lead from the pack to the coil.

Thank you for choosing CDI Electronics

4/20/2009

CDI Electronics • 111 Commerce Circle • Madison, AL 35758  
Fax 256-772-5701 • www.cdielelectronics.com