

Installation and Troubleshooting Guide



CDI P/N: 852-9820

IMPORTANT NOTICE: Disconnect the positive lead from the battery prior to this installation.

WIRE COLOR CONNECTION POINT

Blue Motor "up"
Green Motor "down"
Red +12 volt
Black Ground

Red/White Switch "common"
Blue/White Switch "up"
Green/White Switch "down"

Note: Relay only P/N 852-9819 can be purchased separately

- 1. Disconnect and remove the old trim solenoids and wires, saving the old bolts.
- 2. Install the new relay according to the directions below.

Starboard Side Mounted Relay's (V-6):

- 1. Mount the new trim relays (using the old bolts) on the side of the air silencer.
- 2. Insert the blue and green wires from the new motor into the relay connector, matching the colors.
- 3. Plug the blue/white and green/white wires into the engine harness blue/white and green/white wires.
- 4. Route the red wire in the new harness over to the starter solenoid and connect it with the positive battery cable.

Rear Mounted Relay's (V-6):

- 1. Mount the new trim relays using the coil plate mounting bolts for the ignition coils.
- 2. Route the blue and green wires from the new motor to the relays and insert them into the proper connector, matching the colors.
- 3. Route the blue/white and green/white wires over to the engine harness main connector and connect the blue/white and green/white wires.
- 4. Route the red wire in the new trim harness over to the large red wire terminal on the terminal strip for the regulator/rectifier or to the starter solenoid battery terminal.
- 5. Reconnect the battery cables.
- 6. Work the tilt/trim up and down several times stop to stop.